

BELT DRIVE

Model
MRH 3-10
3-10HP/2,2-7,5kW

Δ Standard Delta Star Starter

CARATTERISTICHE

Trasmissione a cinghia
Filtro olio e disoleatore SPIN/ON
Refrigerazione olio tramite radiatore
elettroventilato
Pannello di prefiltrazione

Belt transmission
Oil separator and oil filter SPIN/ON
Oil/air cooling through electrically
aired radiator
Pre-filtering panel

FEATURES

Controllore Logik
Controller Logik

Radiatore ed elettroventola
Radiator and electric fan

Cabina insonorizzata
Soundproof cabin



QUALITY MADE IN ITALY

IE3 PREMIUM EFFICIENCY MOTOR

Codice Code	Modello Model	Pressure		Power		Flow			Voltage	Noise	Essiccatore Dryer	Tank	Weight	Dimensions
		bar	p.s.i.	HP	kW	l/min	CFM	m³/h						
82001	MRH 3M	10	143	3	2,2	300	10,5	18	400/3/50	65	-	-	140	68x96x82
82003	MRH 3	10	143	3	2,2	300	10,5	18	400/3/50	65	-	-	140	68x96x82
82005	MRH 4	10	143	4	3	400	14	24	400/3/50	65	-	-	145	68x96x82
82007	MRH 5	10	143	5,5	4	550	19,4	33	400/3/50	65	-	-	150	68x96x82
82009	MRH 7	10	143	7,5	5,5	750	26,5	45	400/3/50	66	-	-	155	68x96x82
82011	MRH 10	10	143	10	7,5	950	33,5	57	400/3/50	67	-	-	160	68x96x82

⚡ Voltaggio può essere personalizzabile
The voltage can be customizable

⬆️ Tutti i modelli possono essere anche a 13 o 15 bar
All the models can be at 13 and 15 bar

⬆️ Opzioni Soft Starter ABB per tutti modelli
ABB Soft Starter option for all models