

MINI ROTOR

LA PADANA
AIR COMPRESSORS

Model
MRHD 3-10
3-10HP/2,2-7,5kW

CARATTERISTICHE

Trasmissione a cinghia
Filtro olio e disoleatore SPIN/ON
Refrigerazione olio tramite radiatore
elettroventilato
Pannello di prefiltrazione

*Belt transmission
Oil separator and oil filter SPIN/ON
Oil/air cooling through electrically
aired radiator
Pre-filtering panel*

BELT DRIVE 

FEATURES

Controllore Logik
Controllore Logik

Cabina insonorizzata
Soundproof cabin










Radiatore ed elettroventola
Radiator and electric fan





Essiccatore
Dryer


QUALITY MADE IN ITALY

IE3 PREMIUM
EFFICIENCY MOTOR 

Codice Code	Modello Model													
		bar	p.s.i.	HP	kW	l/min	CFM	m ³ /h	Volt/ph/hz	dB(A)	Essiccatore Dryer	Lt	kg	WxDxH (cm)
83001	MRHD 3M	10	143	3	2,2	300	10,5	18	400/3/50	65	LPE-MR100	-	140	71x68x134
83003	MRHD 3	10	143	3	2,2	300	10,5	18	400/3/50	65	LPE-MR100	-	140	71x68x134
83005	MRHD 4	10	143	4	3	400	14	24	400/3/50	65	LPE-MR100	-	145	71x68x134
83007	MRHD 5	10	143	5,5	4	550	19,4	33	400/3/50	65	LPE-MR100	-	150	71x68x134
83009	MRHD 7	10	143	7,5	5,5	750	26,5	45	400/3/50	66	LPE-MR100	-	155	71x68x134
83011	MRHD 10	10	143	10	7,5	950	33,5	57	400/3/50	67	LPE-MR100	-	160	71x68x134

 Voltaggio può essere personalizzabile
The voltage can be customizable

 Tutti i modelli possono essere anche a 13 o 15 bar
All the models can be at 13 and 15 bar

 Opzioni Soft Starter ABB per tutti i modelli
ABB Soft Starter option for all models