

MAXT AIR

LA PADANA
AIR COMPRESSORS

Model
MXH 1500-2000 /500
15-20HP/11-15kW

CARATTERISTICHE

Trasmissione coassiale
Funzionamento on/off
Filtro olio e disoleatore SPIN/ON
Raffreddamento olio/aria tramite radiatore a ventilazione forzata

Coaxial drive
On/off working
Oil separator and oil filter SPIN/ON
Oil/air cooling through forced ventilation radiator











DIRECT DRIVE 


FEATURES


QUALITY MADE IN ITALY




IE3 PREMIUM 
EFFICIENCY MOTOR

Codice Code	Modello Model														
-	-	bar	p.s.i.	HP	kW	l/min	CFM	m ³ /h	Volt/ph/hz	dB(A)	∅	Essiccatore Dryer	Lt	kg	WxDxH (cm)
35675	MXH 1500-500	8	116	15	11	1650	59	100	400/3/50	66	3/4	-	500	365	82x200x188
35676	MXH 1500-500	10	145	15	11	1500	54	90	400/3/50	66	3/4	-	500	365	82x200x188
35677	MXH 2000-500	8	116	20	15	2200	79	131	400/3/50	66	3/4	-	500	382	82x200x188
35678	MXH 2000-500	10	145	20	15	2000	72	120	400/3/50	66	3/4	-	500	382	82x200x188
35676.1	MXH 1500-500	6-13	85-189	15	11	340-1650	12-57	20-98	400/3/50	66	3/4	-	500	367	82x200x188
35678.1	MXH 2000-500	6-13	85-189	20	15	340-2200	12-77	20-132	400/3/50	66	3/4	-	500	384	82x200x188

 Voltaggio può essere personalizzabile
The voltage can be customizable

 Tutti i modelli possono essere anche a 13 o 15 bar
All the models can be at 13 and 15 bar

 Opzioni Soft Starter ABB per tutti i modelli
ABB Soft Starter option for all models